



7	EPC-CA0010014	extension board	C94 Apple head extension board/size: 10*7.8*7.24 (Model: L06015-1AL1B10)	1	PCS
6	OTH-000000158	Plastic materials	Plastic material 45P PVC material, porcelain white/passed ROHS2.0+REACH +PAHS2	0.008	KG
5	OTH-000000174	Plastic materials	Plastic raw material PE material, low density/transparent/LLDPE wire inner mold/pass REACH/ROHS2.0/SCCP/17P	0.004	KG
4	MMT-CA7902800	tinplate	C94 tinplate/integrated with tail card Material: SUS: 304 L=17mm Size: 7.9*2.8mm	1	PCS
3	ETT-IPH5C8900	MFI IPH5 terminal Child/C48B	MFI IPH5 terminal/C89 charging and data cable dedicated (without iron shell on the terminal head) MFI677-16892 A male to lightning (new)	1	PCS
2	ETC-D04205000	USB2.0 terminal	USB2.0 AM anti-opening white PBT plastic core terminal brass gold plated 1U" iron shell nickel plated 80U" iron shell and the 4th pin short circuit L=20.50mm RoHS2.0	1	PCS
1	EWD-435200015	data line	21AWG (80/0.08TS+500D)*1C+30AWG (11/0.08TS+250D)*2C+D (80/0.08TS+500D)*1C+AL+B (16/5/0.08TS) White PVC outer quilt OD: 3.5mm Cutting line length: 2020±5mm/pass EMC, ROHS2.0, SSCP, PAH	1	PCS
ITEM	PART NO.	NAME	DESCRIPTION	Q'TY	UNIT
8	7	6	5	4	3

Notice:

- 100% free from open circuit, short circuit and dislocation.
- Insulation resistance: DC300V/0.01s, 10MΩ.
- On-resistance: 2Ω.

2. The size marked with "▼" is the key size.

3. The raw materials and processes used in this product must meet the RoHS2.0 related regulations on environmental management substances.

● SHELL	SHIELD	DRAIN+BRAID	● SHELL
5	GND		4
4	NC		NC
3	D+	GREEN	3
2	D-	WHITE	2
1	VBUS	RED	1
P1	SIGNAL	COLOR	P2

WIRE CONNECTION TABLE

X.±1	X°	Customer P/N: AC3012	TITLE: USB2.0 AM TO Lightning(C89)	
.X±0.3	.X°			
.XX±0.20	.XX°	PART NO. FCA2508 FCA2510	DWG NO: FCA2508 FCA2510	
.XXX±0.100	.XXX°			
UNITS:	mm	DRAW: 2021.10.21	CHKD:	
		APPD:		
		SCALE	SHEET	REV.
		1:1	1/1	A0