



# ADDERLINK X Series X-100 Extenders

**Short haul, fully featured, keyboard, video, mouse and optional audio extender for PS/2 and USB computers.**

AdderLink X-100s have been designed for use in applications where keyboard, mouse, high quality video and audio needs to be extended no more than 100m (330ft) over category 5 or higher UTP cable. The AdderLink X-100s provide industry-leading video clarity, audio quality and compatibility.

## FEATURES

### Video performance

Industry leading resolutions of 1600 x 1200 are achievable up to 100m (330ft), 1900 x 1440 up to 50m (165ft).

### Video compensation

The AdderLink X-100 applies signal compensation that allows for smooth and fine adjustments providing great video quality up to 100m.

### Emulated DDC

Unless an extender actively supports DDC some well-known high performance video cards cannot be used at high resolutions. The AdderLink X-100s fully support DDC.

### USB Emulation

When using an X-100 pair to extend a CPU with a USB keyboard and mouse interface, it is ensured that the keyboard and mouse are continually emulated for maximum availability and essential functionality such as country code reporting for Sun CPUs.

### Brightness control


The AdderLink X-100s offer their own brightness correction to ensure images are crisp, clear and bright.

### Audio

Optional digital stereo audio delivers high fidelity audio for speakers.

### Variety of models available

To suit the maximum possible number of applications the X-100 is available in a number of models, PS/2 and video (X-100-PS2/P) PS/2, video and audio (X-100A-PS2/P), USB and video (X-100-USB/P) and USB, video and audio (X-100A-USB/P).





# ADDERLINK X Series X-100 Extenders

Short haul, fully featured, keyboard, video, mouse and optional audio extender for PS/2 and USB computers.

## TECHNICAL SPECIFICATIONS

<b>Video resolutions</b>	1600 x 1200 at distances up to 100m/330ft, 1900 x 1440 at distances up to 50m/165ft
<b>Extension distance</b>	Up to 100m/330ft using CATx cable (x=5,5e,6,7)
<b>Devices supported</b>	Supports any computer with PS/2 or USB style keyboard and mice, flat-screen and CRT style monitors with standard HD-15 video connectors and optional audio through 3.5mm audio jack
<b>O/S compatibility</b>	All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.
<b>Connectors (local)</b>	Video: HDD15 Keyboard Mouse: MiniDin6. Optional audio: 3.5mm jack CATx: 1 x RJ45 connector Or Video: HDD15 Keyboard Mouse: USB type A. Optional audio: 3.5mm jack CATx: 1 x RJ45 connector
<b>Connectors (remote)</b>	Video: HDD15 Keyboard Mouse: MiniDin6. Optional audio: 3.5mm jack CATx: 1 x RJ45 connector. Power: 2.5mm DC jack
<b>Physical (local)</b>	Combination of plastic enclosure and cables. Enclosure: 64mm x 45mm x 25mm Cables: 340mm long
<b>Physical (remote)</b>	All metal case, 123mm x 74mm x 26 mm
<b>Power supply</b>	100 - 240VAC 50/60Hz
<b>Operating temperature</b>	0°C to 40° / 32°F to 104°F
<b>Approvals</b>	CE, FCC

Local, Remote and Global Computer Control



**ADDER CORPORATION**  
29 Water Street, Newburyport, MA 01950 USA  
Tel: +1 888 932 3337 Fax: +1 888 275 1117  
email: [usasales@adder.com](mailto:usasales@adder.com) [www.adder.com](http://www.adder.com)

**ADDER TECHNOLOGY LIMITED**  
Technology House, Trafalgar Way, Bar Hill, Cambridge, CB23 8SQ UK  
Tel: +44 (0)1954 780044 Fax: +44 (0)1954 780081  
email: [sales@adder.com](mailto:sales@adder.com) [www.adder.com](http://www.adder.com)