



LTR	REV.	DESCRIPTION	DATE	APP'D						RoHS-COMPLIANT
-----	------	-------------	------	-------	--	--	--	--	--	----------------




ELECTRICAL TEST:

1. 100% OPEN SHORT MIS WIRE TEST
2. CONTACT RESISTANCE: 3 OHM MAX
3. INSULATION RESISTANCE: 10M OHM MIN
4. HI-POT TEST: DC 300V/10ms
5. Displayport version: 1.1v
6. Max Resolution: 1920*1080P



VGA 15P+PCB' A



NO.	NAME	SPEC	Q'TY	REMARK
6	MOLD	BLACK 45P PVC	A/R	
5	MOLD	LDPE, NATURAL COLOR	A/R	
4	SCREW	#4-40UNC, Ø4.0*L=61MM	2	
3	PLUG	VGA/M:PIN G/F, BLUE PVC CORE, SHELL G/F,+PCB' A(ANX 9833)	1	
2	PLUG	DP 20P/M:PIN G/F, BLACK PVC CORE, SHELL G/F, BLACK PVC SHELL	1	
1	CABLE	UL20276 #32*3P+#32*5C+AEB, BLACK PVC JACKET, OD:5.0mm L=500/1000/1500/2000mm	1	

ITEM: AK3999
DP M TO VGA M BLACK CABLE

C.T

C.T ITEM

Tol.	Inch	mm	UNIT	mm	DRAWING:	HUANG
X.	.02	0.5	ANGLE	±'	CHECK 1:	
X.X	.12	0.3	SCALE	NONE	CHECK 2:	
X.XX	.008	0.2	FONT	NONE	CHECK 3:	
X.XXX	.006	0.15	The third perspective		DATE	2015-09-23
X.XXX	.006	0.15			VER.	A PAGE 1/1

