



NOTE:

- 1.Insertion loss Max :0.2dB
- 2.Insertion loss Typical values:0.1dB
- 3.LC sleeve material:ZrO₂
- 4.Operation temperature:-40°C to +85°C
- 5.LC connector according to IEC 61754-20
- 6.Durability:1000 matings
- 7.Tensile strength:200~600G

ROHS
Compliant

| Part Number | Interface type | Optical fiber type | Color | Material |
|-------------|-----------------|--------------------|--------------|----------|
| EA1018 | LC-LC | OM1/2 | Beige | Plastic |
| EA9008 | LC-LC | OM3 | Aqua | Plastic |
| EA9009 | LC-LC | OM4 | Erica Violet | Plastic |
| EA1019 | LC-LC | OM5 | Lime green | Plastic |
| EA1020 | LC-LC | SM | Blue | Plastic |
| EA1021 | LC/APC8-LC/APC8 | SM | Green | Plastic |

| | | | |
|---------------|-------------------------|----------|-------------|
| Designed by: | Yong Yu | Audit: | Qihua Cheng |
| Date: | 2017-10-11 | Approve: | Yong Huang |
| Unit: | mm | Sheet: | A4 |
| Product Name: | LC 4core flange adaptor | | |
| Drawing NO: | SOP-ED-171011-02-V1 | | |