



ASSEMBLY CONNECTIVITY	
LC/PC-1	LC/PC-2
A	B
B	A

ITEM NO	LENGTH
EL9701	1.00m
EL9702	2.00m
EL9703	3.00m
EL9705	5.00m
EL9710	10.00m

**NOTE:**

- 1.Insertion loss :LC/PC $\leq$ 0.25dB  $\lambda$ : 850&1310nm  
Return loss :LC/PC $\geq$ 30dB  $\lambda$ : 850&1310nm
- 2.Durability:500 matings
- 3.Operation temperature:-40°C to +85°C
- 4.LC connector according to IEC 61754-20

ROHS  
Compliant

LC/PC --- LC/PC DX 2.0mm OM4 LSZH Erika Violet		
ITEM	Description	Q'TY
1	LC dust cover white	4 PCS
2	LC/PC MM simplex connector beige	4 PCS
3	LC clip beige	2 PCS
4	LC 2.0mm boot yellow	2 PCS
5	LC 2.0mm boot white	2 PCS
6	LC heat-shrink tubing yellow	2 PCS
7	LC heat-shrink tubing white	2 PCS
8	Breakout heat-shrink tubing black L=15mm	1 PC
9	OD=2.0mm MM duplex OM4 50/125um fiber optical cable LSZH Erika Violet	1 PC

ewent			
Designed by:	Yong Yu	Audit:	Qihua Cheng
Date:	2018-02-27	Approve:	Yong Huang
Unit:	mm	Sheet:	A4
Drawing NO:	SOP-ED-170314-09-V1		