

ADDERLink™ INFINITY 1002

IP KVM Matrix



Single link, single head digital video and
USB2.0 over a single cable

Features

Perfect digital video, real time control

Using a spatially-lossless encoding system, with 1:1 pixel mapping, ADDERLink™ INFINITY provides pixel-perfect and color accurate video with no artefacts. The digital video you receive is the same as the digital video leaving the remote computer.

Single CATx cable or fiber with immunity from interference

ADDERLink™ INFINITY is engineered to provide a highly robust signaling solution. Giving you the freedom to use the full variety of cable that you find within an average structured network. The result is that you can achieve reliable links, regardless of whether the cables are CAT5e, CAT6 or CAT7.

Unlimited extension distances

Extension distance is not limited to a single 100m / 300ft cable length - If you need to extend further, simply add a 1GbE network device to achieve an additional 100m / 300ft. This can be repeated many times. The units are also fitted with SFP cages to accept fiber optic which enable extension distances of up to 10km / 6 miles with fiber.

Support for MacPro (Dithered Video)

Some graphics cards use a technique called dithering to give the appearance of a deeper color depth than is actually the case. As a result, dithering can significantly increase the normal video data rates. The ADDERLink™ INFINITY 1002 (ALIF1002) features Magic Eye which supports dithering without allowing it to degrade performance.

Redundant network operation

The units are able to detect whether the network is in operation and can automatically change to its second network port if it detects a failure.

USB2.0 with class control

Enables connection of USB devices from mice and keyboards through to graphics tablets, jog shuttles, joysticks and 3D explorers, alongside mass storage devices. For secure applications, the system has the ability to disable the use of non-HID devices, meaning there is no need to physically block USB ports to prevent the use of mass storage devices.

Plug and Play


ADDERLink™ INFINITY extender devices are delivered in a zero config state so you can plug them in and start working on them straight away. There is no need for drivers or software to be installed.

Redundant network operation

The units are able to detect whether the network is in operation and can automatically change to its second network port if it detects a failure.

ADDERLink™ INFINITY Matrix

Adding the ADDERLink™ INFINITY Manager (AIM) you can turn multiple point-to-point extenders into a truly scalable digital KVM matrix system that allows any workstation to link with any computer connected to the network.



Product In Brief

ADDERLink™ INFINITY 1002 is a high performance KVM (Keyboard, Video and Mouse) extender that forms part of the ADDERLink™ INFINITY matrix solution.

This enables you to locate your critical computing hardware in a secure and temperature controlled environment away from the user work station, whilst maintaining a Pixel-perfect desktop experience.

- Plug and play
- 100m / 300ft extension distance on single CATx; unlimited using standard IP network
- From 500m / 1500ft up to 10km / 6 miles over fiber
- Single link or single head configuration
- 1920x1200 @60Hz maximum resolution
- USB mass storage supported plus: keyboard, mouse tablet and touch
- Support for MacPro®
- Redundant network operation

Technical Specifications

Hardware compatibility

- All computers with DVI-D, USB, Audio, RS232 - requirement dependent.

DVI-D - Digital Visual Interface (digital only)

- The system supports a single Link DVI-D resolution to a maximum of 1920x1200 @60Hz.

USB2.0 with class control

- Supports USB2.0 devices (low, full and high speed). Security feature allows the blocking of non HID devices.
- Isochronous devices are not supported (e.g. USB audio or video devices).

Digital stereo audio

- The system transfers analog stereo audio (Line In/Line Out) via digital signalling between any transmitter/receiver pair.
- Additionally, the audio output of any transmitter can be multicast to many receivers.

RS232

- RS232 can be passed between the units to a maximum baud rate of 115,200.
- RS232 is a point to point connection technology and cannot be multicast.

Software compatibility

- All known operating systems.

Computer connections transmitter (TX)

- 1x DVI-D, audio 3.5mm in, audio 3.5mm out, USB type B, RS232 9-pin D-type
- 1x 8p8c and 1x SFP for ADDERLink™ INFINITY network connections.

Peripheral connections receiver (RX)

- 1x DVI-D, audio 3.5mm in, audio 3.5mm out, 4x USB Type-A, RS232 9-pin D-type
- 1x 8p8c and 1x SFP for ADDERLink™ INFINITY network connections.

Physical design

- 1U compact case, robust metal construction.
- 198mm/7.92" (w), 44mm/1.76" (h), 150mm/6.0" (d), 1.1kg/2.7lbs.

Power

- 2.5mm DC jack (power adapter included), 100-240VAC 50/60Hz, 0.8A, input to power adapter.
- 5VDC 20W output from power adapter.

Operating temperature

- 0 to 40°C / 32 to 104°F.

Approvals

- CE, FCC.



ALIF1002 - Rear View



ALIF1002 - Front View

Ordering Information

ALIF1002P-XX: ADDERLink™ INFINITY pair including TX and RX units

ALIF1002T-XX: ADDERLink™ INFINITY TX (transmitter unit only)

ALIF1002AT-XX: ADDERLink™ INFINITY TX (VGA transmitter unit only)

What's in the Box?

RX: AIF1002R and PSU + IEC mains cable

TX: AIF1002T, PSU + IEC mains cable, USB cable, DVI cable and 2 x Audio cable

XX = Mains Lead Country Code:
UK = United Kingdom
US = United States
EURO = Europe
AUS = Australia
JPN = Japan

Additional Accessories

RMK4V: VESA mounting bracket (screws included), can also be used to secure to walls and other surfaces

Two 19" rack mount brackets (screws included):

RMK4S: One unit per 1U rack slot

RMK4D-R2: Two units per 1U rack slot

VSCD1: Single link DVI-D to DVI-D video cable

VSC24: USB cable 2m / 6ft (USB Type-A to B)

SFP-MM-LC: Multimode fiber optic module with LC connectors for up to 500m / 1500ft

SFP-SM-LC: Single mode fiber optic module with LC connectors for up to 10km / 6 miles

SFP-CATX-RJ45: SFP to CATx converter module

PSU-RPS-5V: 12v to 5v power adaptor, compatible with ADDER RED-PSU

About Adder

Adder is a leading developer and thought leader in connectivity solutions. Adder's advanced range of KVM switches, extenders and IP solutions enable the control of local, remote and global IT systems across the enterprise.

The company distributes its products in more than 60 countries through a network of distributors, resellers and OEMs.

Adder has offices in China, Germany, Japan, the Netherlands, Singapore, Spain, France, Sweden, United Kingdom and United States.

To find out more, visit: adder.com

Global Headquarters

Tel: +44 (0)1954 780044 | Fax: +44 (0)1954 780081
Email: sales@adder.com

Americas

Tel: +1 888 932 3337 | Fax: +1 888 275 1117
Email: usasales@adder.com

Asia Pacific

Tel: +65 6288 5767 | Fax: +65 6284 1150
Email: asiasales@adder.com

All brand names and trademarks are the property of their respective owner. Copyright 2020 | Adder Technology Ltd. | ADDER_DS004_EN_v7_FINAL_LL

Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only.

ADDER[®]
THE IP KVM PEOPLE

DATA
SHEET