



CROSS-SECTION VIEW
(SCALE 4:1)

ITEM	DESCRIPTION	
1 CONDUCTOR 4 CORES	MATERIAL	TIN COPPER WIRE
	STRANDED	7/0.2mm
	AWG	24 AWG
	TWISTED PAIR	2 - BLUE /RED & ORANGE/WHITE
	DCR	<24Ω/m
2 INSULATION	MATERIAL	FM-PE
	THICKNESS	0.25mm
	O.D	1.27 ± 0.5mm
3 INSULATION	MATERIAL	100% AL FOIL PLUS 25% OVERLAP
	AWG	24 AWG
4 DRAIN	MATERIAL	TIN COPPER WIRE
	STRANDED	7/0.20mm
5 BRAID SHIELDING	MATERIAL	TINNED COPPER WIRE
	STRANDED	16x7/0.12mm MIN 65% SHIELDING
	PITCH	25mm ± 2mm
	RESISTANCE	<10MΩ/Km
6 JACKET	MATERIAL	PVC (HALF MATT BLACK CL2)
	THICKNESS	0.76mm MIN
	O.D	6.9mm ± 0.3mm
ELECTRICAL	CAPACITANCE	<41pF/m
	IMPEDEANCE	100 ± 15Ω

Amphe-DMX by **Amphenol®** CA-D-BLK
95 mm REF

UNLESS OTHERWISE SPECIFIED TOLERANCE TO BE		THIS DOCUMENT IS THE PROPERTY OF AMPHENOL AUSTRALIA PTY. LTD.. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER				0	FIRST ISSUE	MH	10-03-09	----
LINEAR	ANGULAR	CAD FILE: 53730042100120	DRN: MH	DATE: 03-03-09	TITLE:	REV.	CHANGE DETAILS	BY	DATE	CHG/No
X ± 0.5	X° ± 1°	MATL: REFER TO COMPONENT	CKD: S.R	DATE: 10-03-09	DMX Cable 2 PAIRS CUSTOMER DRAWING	Amphenol				
X.X ± 0.1	X°X' ± 30'	DO NOT SCALE	FINISH: REFER TO COMPONENT	DATE: 10-03-09		Amphenol Australia Pty.Ltd, 2 Fineways Blvd, Keysborough, Vic.3173				
X.XX ± 0.05	X°X'X" ± 15"	DIMENSIONS IN MILLIMETRES		THIRD ANGLE PROJECTION	SCALE: 2:1 UOS	PART No: CA-D-BLK-100	SIZE: A4	DRAWING NO. 53730042-100-2		SHEET 2 OF 2