



ASSEMBLY	CONNECTIVITY
ST/UPC-1	ST/UPC-2
1	2
2	1

ITEM NO	LENGTH
EL1001	1.00m
EL1002	2.00m
EL1003	3.00m
EL1005	5.00m

**NOTE:**

1. Insertion loss :ST/PC<0.25dB A: 850&1310nm  
Return loss :ST/PC>30dB A: 850&1310nm
2. Durability:500 matings
3. Operation temperature: -40°C to +85°C
4. ST connector according to IEC 61754-2

**ROHS  
Compliant**

ST/PC --- ST/PC DX 2.0mm OM1 LSZH Orange

ITEM	Description	Q'TY
1	ST dust cover Lucency	4 PCS
2	ST/PC MM simplex connector	4 PCS
3	ST boot red	2 PCS
4	ST boot black	2 PCS
5	Cable marker:1~2	2 PCS
6	Breakout heat-shrink tubing black L=15mm	2 PCS
7	OD=2.0mm duplex OM1 62.5/125um fiber optical cable LSZH Orange	1 PC

**ewent**  
Brand

Designed by:	Yong Yu	Audit:	Qihua Cheng
Date:	2017/3/14	Approve:	Yong Huang
Unit:	mm	Sheet:	A4
Drawing NO:	SOP-ED-170314-10-V2		