



| No. of Positions | Dimensions(mm) | | | | | |
|------------------|----------------|-------|-------|-------|-------|-------|
| | A | B | C | D | E | F |
| 9 | 30.81 | 24.99 | 16.92 | 16.33 | 11.09 | 10.16 |
| 15 | 39.14 | 33.32 | 25.50 | 24.66 | 19.39 | 17.78 |
| 25 | 53.04 | 47.04 | 38.96 | 38.38 | 33.24 | 30.48 |
| 37 | 69.32 | 63.50 | 55.42 | 54.84 | 49.86 | 45.72 |

Tolerances +/-0.15mm

- Insulator: Glass-filled thermoplastic, PBT, UL94V-0 rated
- Contact: Brass
- Contact resistance: 20mOhm max. at 1A DC
- Insulation resistance: 1000Mohm at 500V DC
- Dielectric withstanding voltage: 1000V ACrms 60Hz for 1 minute
- Current rating: 5A
- Voltage rating: 250V ACrms, 60Hz

| Änderung | Datum | Name | Datum | Name |
|----------------------|----------|---------|----------|----------------|
| Tolerances completed | 12.07.01 | Hellwig | 09.02.00 | Hellwig |
| | | | 09.02.00 | <i>Hellwig</i> |
| | | | Norm. | |

Benennung
D-Sub flat cable connector
 A-DFF... LP III/ Z
 A-DSF... LP III/ Z

| | | |
|---------------------------------------|--|------------|
| Zeichnungsnummer | | Blatt |
| ASSMANN ASS 0128 CO | | 1/2 |
| Ersatz für ASS 0128 CO vom 08.10.1999 | | Blatt |

ASSMANN
 Electronic Components